

City of Asheville Water Resources Department Approved Manufacturers Products List

1. Ductile Iron Class 350 Water Pipe:

- American Cast Iron Pipe Co.
- Griffin Pipe
- U. S. Pipe
- Atlantic States

2. Fire Hydrants AWWA C-502, ASTM B-61, B-62 or B-96,250 PSI rating:

- Clow Medallion
- American MK-73-5
- Mueller Super Centurion 250

3. Resilient Seated Gate Valves (4" through 10") 250 PSI Rating, AWWA C-500 and AWWA C-509:

- Clow
- American Flow Control Series 2500
- Mueller 2360 Series
- M&H 4067-01
- U.S. Pipe Metro Seal 250

4. Butterfly Valves (> than 10"), 250 PSI rating

- Mueller
- Dezurik
- M & H

5. Resilient Seated Tapping Valves MSS SP60, Two Piece type

- Clow
- Mueller
- American Flow Control

6. Wafer Valves

• Kennedy Fig. 706

7. Spring Loaded Check Valves AWWA C-508

- Muller A-2600-6-01
- American Series 50

8. **Air Release Valves:**

- Golden Anderson GA-920
- Apco 200 A
- Empire
- Crispin AR-10

9. **Control Valves (Pressure Reducing , Pressure Sustaining, etc.)**

- Ross
- Cla-Val

Automatic Flushing Valves 10.

- Kupferle Foundry Company
- Hydro-Guard

Water Service Fittings (Lead Free Brass) 11.

(Approved Manufacturers) Ford, A Y McDonald

APPROVED PARTS LIST

A.Y. McDonald	FORD	MUELLER
5/8 inch Meter Setter		
14-1 Iron Yoke Bar 714-1EHG Expansion Connection 76102 WYT 3/4x5/8x01 Straight Ball Valve 711-3YF 23 In Line Dual Check 74704-22 ¾" Corp Stop	Y501 EC 1-NL B94-213W-Q-NL HHS91-313-NL FB1100-3-Q-NL	5/8" H-5010 5/8" H-14234N B-24359N H-14247N 3/4" B25028N
¾ inch Meter Setter		
14-3 Yoke Bar 714-2EHG Expansion Connection 76102 WYT 3/4x5/8x02 Straight Ball Valve 711-3YF 33 In Line Dual Check 74704-22 3/4" Corp Stop	Y503 EC 23-NL B94-223W-Q-NL HHS91-323-NL FB1100-3-Q-NL	34" H-5030 34" H-14234N B-24359N H-14247N 34" B25028N
1" Settings		
14-4 Iron Yoke Bar 714-4EHG Expansion Connection 76102-22 1x3/4x04 Straight Ball Valve 74704-22 1" Corp Stop 1 ½" Settings	Y504 EC 4-NL B94-344W-Q-NL FB1100-4-Q-NL HHS91-344-NL (Check)	1" H-5040 1" H-14234N 1" B-25359N 1" B-25028N
720B612WDFF 665 1 ½" Meter Setter 73131B 2" Corp Stop	VBHH76-12B-11-66-NL FB500-7-NL	1 1/2x12 B-2423 2" B-2969N

2" Settings

720B712WDFF 775 2" Meter Setter 73131B 2" Corp Stop

VBHH77-12B-11-77-NL 2x12" B-2423 FB500-7-NL 2" B-2969N

12. Misc Water Service Fittings:

Any brass part of the fitting or valve <u>not</u> in contact with potable water shall be made of 85-5-5-5 brass as defined for this specification as UNS Copper Alloy C83600 per ASTM B30, ASTM B62, ASTM B584 and AWWA C-800. Water service fittings included in this specification are: Unions, Nipples, Bushings, Couplings & Tees as manufactured by Merit Brass or approved equal.

13. Copper Service Pipe:

• Type "K" conforming to ASTM B-99

14. Service Line Tapping Saddles (double straps, 250 PSI rating):

- Mueller DR2A
- Smith Blair 313
- Ford F202
- Romac 202

15. Air Release Valves:

Golden Anderson GA-920 Apco 200 A
 Empire Crispin AR-10

16. Joint Restraint

- Ebaa Iron (Mega Lug)
- Sigma One Lok
- Ford Uni-Flange 1400 Series
- Star Pipe Products
- Smith Blair ("Cam-Lock Series 111/120)

17. Tapping Sleeves (Ductile Iron / Mechanical Joint Full Body)

- Mueller
- Clow
- American

18. Pre-manufactured Concrete Vaults:

- Tindall
- Old Castle
- Southern Concrete

19. Above Ground Enclosures:

• UL Approved / Heated

20. Miscellaneous Castings:

• U.S. Foundry & Manufacturing Corp.

21. Cast Iron and Ductile Iron Fittings

- All cast iron and ductile iron pipe fittings shall be mechanical joint in accordance with ANSI Specification A 21.10 for underground piping. All ductile iron and cast iron pipe fittings shall be flanged in accordance with ANSI Specification B 16.1 for exposed piping.
- All fittings shall be lined with cement mortar not less then 1/16-inch thick in conformance with ANSI Specification A 21.4 and suitable for a minimum of 250 psi working pressure unless otherwise specified.
- All mechanical joints shall be manufactured in accordance with ANSI Specification A 21.11.

22. Double Leaf Vault Access Doors:

- Halliday Products
- Bilco

23. Automatic Meter Reading Device

• Neptune R900 Wall and Pit FR MIUS

** Substitute products will not be considered on a project by project basis.

Manufactures can submit alternate material product information for review by the Water Resources Department for inclusion on the approved product list.